



BELPROTECT

PRODUCT IDENTIFICATION

Belprotect

DESCRIPTION

Belprotect is a colourless coating used to improve the resistance of the coated surface. It contains additives that protect the film against mould and algae.

COMPOSITION

Alkyd resins, non-aromatic solvent, waxes, dryers, UV absorbers and film preservatives.

CHARACTERISTICS

Belprotect is a high-build woodstain used as the final finish on wood that is already coated with a decorative coating.

Belprotect is not a biocidal product and is not intended to protect wood from wood pests such as fungi and insects. For this, we recommend the use of impregnations, such as Belles or Impregnant.

With Belprotect, the coated surface retains its pre-coat color. The product is also suitable as a top coat over dark-colored surfaces.

AREA OF APPLICATION

Belprotect is used in shaded areas that are frequently exposed to humidity and condensation, and where algae are very likely to occur. The coating is not suitable



for the protection of raw wood or wood that has only been impregnated. The final appearance of the surface is glossy.

COLOR

Colourless

SURFACE PREPARATION

Before application, clean the existing coating of all impurities, slightly sand it and remove the dust.

APPLICATION METHOD

Mix before use, do not thin. Apply one coat with a brush or roller onto dry wood that has already been coated. Between coating and drying, the temperature should be above +8 °C.

DRYING

Under normal weather conditions, the drying time is 24 hours. When coating wooden elements that will be mechanically loaded, dry them for a week before loading.

CONSUMPTION

1 l of Belprotect covers 15-25 m² of surface.

CLEANING TOOLS

After use, clean the tools and accessories with Belsol, but also with white spirit or other thinners for synthetic paints.





ADVICE AND WARNINGS

The product is not suitable for restoring decorative coatings. Do not apply on a damaged coating. Clean a worn and algae-infected coating with Algid according to the instructions and restore with Belton or Beltop. Apply Belprotect as the final coat. We recommend systematic protection for the quality protection of wood that is in places exposed to humidity. Pre-protect raw, sanded wood with Belles and two coats of Beltop or three coats of Belton in the desired shade. Apply Belprotect as the final coat.

Avoid coating in strong sunlight.

STORAGE AND HANDLING

Store the product in its original, tightly closed packaging in a dry, covered place at a temperature under 30 °C. Store out of reach of children and separately from food, feed and drinks.

EXPIRATION DATE

In accordance with the stated storage conditions, until the date indicated on the packaging.

ENVIRONMENT

Do not pour liquid waste or agent remains onto the soil, into surface waters or into the sewage system! The agent is harmful to aquatic organisms. Keep out of reach of children. Avoid release into the environment.

Dispose of liquid waste at a hazardous waste collection center. Dispose of liquid waste and the packaging as special waste into collection centers for hazardous waste which are organized by the local service provider for the collection and transport of household waste.





REGULATIONS

In connection with regulations governing product safety, safety at work and transport, read the material safety data sheet.

ADDITIONAL TECHNICAL INFORMATION

More information can be obtained from our distributors or visit our website:

www.belinka.com.

. The purpose of technical information is to inform users about the possibilities of product use and its technical properties. Although the advice is based on long-term experience, it does not exempt the user from making sure the product is suitable for use in their specific case. Due to numerous possible effects on the properties of the product, including the type and quality of wood, the method and conditions of application, the experience of the user, and the conditions of use, we cannot take any responsibility for material damage incurred when using the product. In the event of doubt, please call our advisory service.

Dokument: T_BELINKA_Belprotect_1AN.docx, Revision: 0
Date of revision: 03.03.2020

Helios TBLUS, d.o.o. • Member of KANSAI HELIOS. • Količevo 65, SI-1230 Domžale, Slovenija
T +386 (0)1 588 62 99, **E** info@belinka.si, www.belinka.com



belinka